01 / RANGE GUIDE

Choose your BlackOut blind

Compare the operating system first. Then check the window, fitting position and fabric with AdamsBlinds before ordering.



BlackOut Touch

Hand-operated spring system.



BlackOut Plus

Chain or rechargeable motor.



BlackOut Smart

Motorised, with connected options.

Planning point	BlackOut Touch	BlackOut Plus	BlackOut Smart
Operation	Bottom handle with a spring mechanism	Chain, or a rechargeable motor option	Rechargeable motor with compatible controls
Published maximum width	1,900 mm	2,400 mm	2,400 mm
Published maximum height	1,600 mm	2,400 mm	2,400 mm
Fitting positions	Inside the recess or at its front edge	Inside the recess or on the wall surface	Inside the recess or on the wall surface
Remote control	Not available	With the motorised option	With a compatible remote
App and voice control	Not available	Matched motor and hub required	Matched hub and supported platform required

Maximum dimensions are planning limits, not approval for a particular window. Minimum sizes, fabric choice, controls and clearances must be checked for the exact order.

01 / RANGE GUIDE

Check the window and the details

A cassette blind works as a complete assembly: fabric, top cassette, side rails and lower seal. Its position matters as much as its size.

Clearance figures for initial planning

System	Recess depth to discuss	Important distinction
BlackOut Touch	At least 50 mm	Check the intended position against handles and the opening window.
BlackOut Plus	At least 120 mm	Its top cassette is 78 mm high and 86 mm deep. Cassette depth is not the complete recess clearance.
BlackOut Smart	At least 120 mm	Confirm the selected assembly, handle clearance and charging access.

These are planning figures for the current range. The selected configuration and the actual window must be checked before final manufacture. Surface fitting needs suitable clear wall space and a sound fixing surface.

What to decide before requesting a quote

- ☐ **Everyday use:** can you reach the bottom handle or chain comfortably, or would remote operation be easier?
- ☐ **The window:** show the opening direction, handles, vents, sill and all four edges. Angled recesses, bays and roof windows are outside the standard application.
- ☐ **The finish:** shortlist fabrics and request samples. Screen colour is indicative; final availability and specification are confirmed.
- ☐ **The service:** choose made-to-measure supply only or an agreed measuring and installation service. Final measurement format is recorded before order.

Useful operating rule
Fully raise the blind before opening the window, and keep it raised while the window is open. Light entering through other parts of a room is outside this blind system.

Start with an initial estimate
Send your postcode, number of windows, approximate opening sizes and photographs. Initial estimates by email or WhatsApp are free. Use the collection enquiry form or contact the team below.