HEXACELL COLLECTION

SLIDERSCREEN SYSTEMS

Hexacell Sliderscreen Mini

Product reference: Sliderscreen Mini

A slim 16 mm cellular blind for suitable bifold doors, square glazing beads and shutter applications. Fabric colours are confirmed on enquiry.



- Slim frame for restricted glazing details
- Manual up-and-down or sideways layouts
- Assessed options for doors, loft windows and shutters

Key specifications

Specification	Detail
Cellular material	16 mm
Semi-flush recess depth	Approximately 19 mm on a suitable square-edged profile
Frame flange	5 mm; excluded from the nominal frame-size definition
V-Screen: sideways movement	Minimum width and drop 200 mm; maximum width 2300 mm and drop 1500 mm
H-Screen: up-and-down movement	Minimum width and drop 174 mm; maximum width 1500 mm and drop 2300 mm
Draw arrangement	One-way draw
Frame colours	White and Black with smooth finish; Dark Grey and Dark Coffee with textured finish
Fabric colours	Blackout and light-filtering choices confirmed with the quotation

View the current choices and request a quotation

07849 709975 | info@adamsblinds.co.uk

www.adamsblinds.co.uk/hexacell-collection/

Options to discuss

- Standard or reverse-facing handle
- Appropriate adhesive fixing or assessed small-screw fixing
- Blackout or light-filtering material; request the current sample choices

Before you order

- Not recommended for lantern-roof installations.
- One-way draw only; do not specify a split-stack Mini.
- The nominal frame dimensions exclude the flange; do not order from glass size alone.
- Adhesive fixing is surface-dependent and does not guarantee damage-free removal.

Bifold doors need a movement check

Show the door both closed and folded, including the gaps between adjacent panels. A frame that fits the glass area may still meet another panel as the door opens. We assess the chosen fitting position before confirming suitability.

Behind shutters, check the louvres

The blind’s frame, fabric stack and handle all sit behind moving parts. Existing shallow shutter frames can require restrictions on louvre movement. For new shutters, frame depth and the blind position are best planned together.

Handle position and service access

Standard and reverse-facing handles suit different installations. An adhesive fixing can give a discreet finish on an appropriate surface, but future removal and the condition of the substrate still need consideration.

View the current choices and request a quotation