SLIDERSCREEN SYSTEMS

Hexacell Sliderscreen PRO

Product reference: Sliderscreen PRO

A stronger framed system for windows and suitable doors, with single- or double-frame builds and optional dual fabrics or insect mesh.



- Window and assessed door configurations
- Double-frame option for greater support and service access
- Dual-fabric combinations can pair privacy fabric with mesh or sheer

Key specifications

Specification	Detail
Native cellular fabric	25 mm; Cellotex Cellect range
Frame builds	Single inner frame or inner and outer double frame
H-Screen: up-and-down movement	Maximum width 1500 mm; maximum drop 2000 mm
V-Screen: double frame	Maximum width 2950 mm; maximum drop 2400 mm
V-Screen: single frame, mesh	Recommended maximum width 2000 mm; drop 2000 mm
V-Screen: single frame, cellular or sheer	Recommended maximum width 2000 mm; drop 1600 mm
Profile colours	White or Black
Door detail	Low-threshold door bar in an assessed configuration

View the current choices and request a quotation

07849 709975 | info@adamsblinds.co.uk

www.adamsblinds.co.uk/hexacell-collection/

Options to discuss

• Single or double frame, subject to size and fitting method

• H-Screen or V-Screen movement with an agreed stack

• Cellular blackout or light-filtering fabric, sheer or insect mesh

• Compatible dual-fabric pairings with magnetic meeting rails

Before you order

• H-Screen drops above 1600 mm are less favourable where long-term tension retention is a priority.

• Outside-recess fitting requires a double frame.

• PRO and LITE profiles, plastic colours and fabrics should not be treated as interchangeable.

• Mesh is an insect-screening material; it is not a security barrier or fall protection.

Choose the frame around the opening

For outside-recess fitting, PRO requires the double-frame arrangement. Door builds use a low-threshold bar, whose position still needs to be considered in the walking route. Include floor, sill and handle photographs with your enquiry.

Plan a comfortable sideways draw

Large single panels require more effort to move. A split stack is recommended above 2000 mm width on a double-frame V-Screen. The best meeting position depends on the opening, furniture and how you normally use the door.

Light control depends on the whole build

A double frame improves the treatment of the corners. Black profiles with compatible black blackout fabric are the strongest starting point where room darkening is the priority. We will assess the frame perimeter and fitting surface as part of the specification.

View the current choices and request a quotation

07849 709975 | info@adamsblinds.co.uk

www.adamsblinds.co.uk/hexacell-collection/