TEMPORARY PAPER BLINDS

Hexacell Temporary Pleated Blinds

Product reference: Temporary Pleated Blinds

Trim-to-size pleated paper blinds for short-term privacy. White filters daylight; black gives a dimout effect. Ask AdamsBlinds about supply.



- A straightforward temporary window covering
- Trim the paper width with scissors
- Choose a lighter white finish or black dimout

Key specifications

Material	Pleated paper
Standard sheet width	914 mm; trimmed to suit
Designed drop	1800 mm
Colour choices	White light-filtering or Black dimout
Adjustment	Pleats held with two supplied clips
Fixing	Adhesive header on a suitable prepared surface

Options to discuss

- White light-filtering paper
- Black dimout paper
- Ask about additional clips and compatible replacement tape
- Overlapping or joining may suit a wider or taller opening; confirm the layout first

Before you order

- Temporary paper covering; not a substitute for a permanent framed blind.
- Not recommended for conservatory roofs.
- Keep paper away from naked flames and keep small clips and fixings out of children’s reach.
- No guarantee of residue-free or damage-free removal on every surface.

View the current choices and request a quotation

07849 709975 | info@adamsblinds.co.uk

www.adamsblinds.co.uk/hexacell-collection/

Useful while the room is changing

Moving in, repainting and waiting for bespoke blinds are common reasons to use a temporary covering. Work out whether the window needs to open during this period, and keep the covering clear of handles, vents and the intended opening route.

Prepare the fixing surface

The fixing area needs to be clean, dry and compatible with the adhesive. Avoid fresh paint and wallpaper. Removal can leave adhesive residue, especially after a long installation; check the surface before choosing a fixing or cleaning product.

Adjusting and replacing the blind

Gather the pleats and use the clips to hold the chosen level. Release them to lower the sheet. Tell us if you need extra clips for a cut-down or replacement arrangement. Paper condition and fitting surface determine whether a covering can be reused.