03 / CUSTOM PLANNING

Five readings for a custom skylight blind

Use this sheet to record the window for an initial assessment. These are window readings, not finished blind sizes, and do not confirm that the product will fit.

Room / window reference and roof-window brand, if known

Reading	Where the reading is taken	Current assessment band	Your reading
Internal frame width	Across the front of the frame, between its two inner edges.	372-1,160 mm	_____ mm
Internal frame height	At the front of the frame, between its top and bottom inner edges.	300-1,350 mm	_____ mm
Visible glass width	Across the visible glass between the glass edges, along the glass surface.	350-1,160 mm	_____ mm
Visible glass height	Between the top and bottom edges of the visible glass, along its surface.	278-1,350 mm	_____ mm
Frame depth	From the glass surface to the front edge of the window frame.	43-80 mm	_____ mm

Keep frame and glass readings separate

The frame may taper towards the glass. A frame width and a glass width describe different positions. Do not substitute one for the other, average the values or add a general fitting allowance.

The five bands are independent assessment limits. A set of readings within the bands still needs a full compatibility check; the numbers are not a universal width-by-height ordering envelope.

Differences, taper, uneven areas or uncertain readings

03 / CUSTOM PLANNING

Check the complete window

A custom size still needs a suitable frame and operating position. Fixed horizontal rooflights and roof lanterns need a different assessment.

Photographs and access information

- ☐ The whole roof window from inside, with the frame and every corner in view.
- ☐ Close views of the top, side and bottom frame, including handles, hinges and existing blind fittings.
- ☐ A view showing the relationship between the glass and the front of the frame; identify any trim or taper.
- ☐ The roof-window label if present, plus a room view showing the height and access.

Number of blinds and whether the windows are identical

Preferred fabric / frame finish and supply or installation service

Postcode, contact name and telephone number

Specification point	What we will confirm
Operating system	This custom range is a manual spring-operated blind. A custom solar version is not assumed available.
Frame and fabric	Silver or White frame choices, plus the final fabric and current availability for the proposed configuration.
Window suitability	The complete frame and glass dimensions, profile, clearances and accessible operating position.
Final order information	The measurement method and information required for manufacture, agreed before the order is placed.

Next step
Send the completed details to AdamsBlinds. Initial estimates by email or WhatsApp are free. A measuring and installation service can be discussed for your postcode and access requirements.