PRODUCT SELECTION / EXTERIOR SHADING

Angled Louvre Screens

Exterior sliding timber screens with fixed angled louvres, giving a consistent horizontal pattern across glazing or a façade opening.



Product illustration. The agreed specification and finish determine the supplied product.

Angled Louvre Screens use fixed timber blades within a framed panel. The angle of the louvres creates a repeating horizontal screen, while the complete panel moves along its specified track.

They can be considered where the building design needs an exterior sliding screen without a separate mechanism for tilting every blade. Moving the panels changes the amount of the opening that is covered.

- A consistent angled-louvre appearance
- Sliding access to the opening
- Timber finish coordinated with the façade

At a glance

Material	Cedar, hemlock or pine as specified
Louvre type	Fixed angled timber blades
Louvre width	55 mm in the listed construction
Panel thickness	40 mm in the listed design
Movement	Sliding panel arrangement

Selection guide, not a technical certificate or confirmed order specification. Dimensions, finishes and availability are agreed in your quotation.

ANGLED LOUVRE SCREENS

Planning your specification

Options to discuss

- Compatible exterior timber finishes
- Panel count and stacking direction
- Reveal or wall-face installation
- Project-specific track and lower guidance

Practical points

- The individual louvres do not tilt.
- Privacy varies with the angle of view.
- Support, exposure and parked-panel space must be confirmed.

A fixed blade arrangement

The listed design uses 55 mm louvres within a 40 mm panel construction. Cedar, hemlock and pine are the documented timber choices. Paint or stain is selected to suit the timber and intended exposure.

Because the louvres are fixed, the view through the screen changes with your viewing angle and the lighting. Discuss the desired privacy and daylight effect before choosing the louvre orientation.

Plan how the panels clear the opening

Sliding panels need space to overlap or park beside the glazing. Reveal-mounted and wall-face arrangements create different relationships with doors, handles, sills and the surrounding façade. The frame, track and number of panels are selected together.

We confirm the upper support, any lower guidance and the access required for maintenance. Exposure and the safe operating position also need assessment. Where several screens form a continuous elevation, the frame alignment and timber finish should be coordinated across the whole project.

Ask about Angled Louvre Screens

Send your postcode, approximate quantity, opening sizes and photographs. Tell us whether you need supply only or measuring and installation.

View the product and request a quotation

info@adamsblinds.co.uk | 07849 709975