PRODUCT SELECTION / EXTERIOR SHADING

Broad Slat Screens

Exterior sliding screens with fixed broad timber slats, creating a calm horizontal surface across balconies, glazing or façade openings.



Product illustration. The agreed specification and finish determine the supplied product.

Broad Slat Screens form a horizontal timber screen within a moving panel. Their broad, flat members create a different appearance from narrow square profiles or traditional angled louvres.

They can be considered where the façade needs a measured rhythm of timber and open gaps. The panel arrangement is designed around the opening, the view and the space available for the screens to slide.

- Broad horizontal timber lines
- A practical sliding screen arrangement
- A finish coordinated with the surrounding architecture

At a glance

Material	Cedar, hemlock or pine as specified
Slat section	70 × 15 mm in the listed design
Slats	Fixed
Panel thickness	40 mm in the listed construction
Operation	Sliding panel layout

Selection guide, not a technical certificate or confirmed order specification. Dimensions, finishes and availability are agreed in your quotation.

BROAD SLAT SCREENS

Planning your specification

Options to discuss

- Compatible exterior stains or paints
- Panel dimensions and overlaps
- Track and parked-panel position
- Coordinated layouts for wider elevations

Practical points

- The slats do not tilt individually.
- The screen is not a substitute for a required safety barrier.
- Exposure, support and maintenance requirements must be confirmed.

Keep the slat arrangement clear

The listed construction uses 70 mm wide, 15 mm thick fixed slats within a 40 mm panel. Cedar, hemlock and pine are the documented timber choices, with an appropriate exterior finish agreed for the project.

The slats remain fixed as the complete panel moves. Their spacing and the viewing angle determine the degree of screening. A broad slat does not, by itself, establish complete privacy or any particular solar-performance figure.

Plan the complete exterior assembly

A screen across a balcony or door opening must work with access, the railing, surrounding cladding and any threshold detail. The track position and parked panel width are therefore part of the initial design, not simply installation details.

We review structural support, exposure and maintenance access before confirming the specification. Timber grain and tone vary naturally, and exterior finishes need appropriate upkeep. Drawings and photographs of the full elevation help us coordinate panel divisions and finish selection across a larger scheme.

Ask about Broad Slat Screens

Send your postcode, approximate quantity, opening sizes and photographs. Tell us whether you need supply only or measuring and installation.

View the product and request a quotation

info@adamsblinds.co.uk | 07849 709975