PRODUCT SELECTION / EXTERIOR SHADING

Sectioned Louvre Screens

Exterior timber screens with a sectioned fixed-slat arrangement, providing a strong linear pattern within a moving panel.



Product illustration. The agreed specification and finish determine the supplied product.

Sectioned Louvre Screens offer a more pronounced linear timber design for exterior openings. The slats form a fixed arrangement within the panel, with divisions and details contributing to the overall pattern.

They can be used to explore a bolder façade treatment than a conventional horizontal Venetian. Access and screening are managed by moving the complete panel rather than tilting individual slats.

- A strong linear timber screen
- Coordinated façade panel groupings
- A distinct alternative to an adjustable Venetian

At a glance

Material	Cedar, hemlock or pine as specified
Slats	Fixed timber slats, 70 mm in the listed design
Panel construction	40 mm in the listed specification
Layout	Panel pattern and movement confirmed for the project

Selection guide, not a technical certificate or confirmed order specification. Dimensions, finishes and availability are agreed in your quotation.

SECTIONED LOUVRE SCREENS

Planning your specification

Options to discuss

- Compatible timber paints or stains
- Agreed slat and frame pattern
- Suitable panel movement arrangement
- Coordinated layouts across several openings

Practical points

- The slats are fixed, with no individual tilt control.
- Pattern details must be confirmed from the selected construction.
- Exterior support, exposure and maintenance requirements apply.

Define the panel pattern

The listed construction uses 70 mm fixed timber slats within a 40 mm panel, with a broader visible frame detail. Cedar, hemlock and pine are the documented timber choices. The exact slat arrangement and any decorative detail are confirmed from the selected design.

The pattern should be considered across the whole elevation. Frame divisions, adjacent panels and the position of doors or glazing can change how the repeated lines are read. A small finish sample establishes colour but cannot explain the complete panel geometry.

Choose the movement around the building

Suitable sliding and other specifically engineered panel arrangements can be assessed for the opening. Track position, clearances and the parked area must be agreed with the surrounding façade and any route through the opening.

We check structural support, exposure and maintenance access before confirming manufacture. Exterior timber requires a suitable treatment and an appropriate care routine. For a wider scheme, send elevations or drawings so the panel grouping can be planned consistently.

Ask about Sectioned Louvre Screens

Send your postcode, approximate quantity, opening sizes and photographs. Tell us whether you need supply only or measuring and installation.

View the product and request a quotation

info@adamsblinds.co.uk | 07849 709975